

## Product Specification

NW Capacity	225L	504L	1000L	1700L	Customize
Inner size (W*D*H)(cm)	70*46*70	80*70*90	100*100*100	120*120*120	Customize
Outer size (W*D*H)(cm)	100*195*210	110*225*230	130*265*245	150*360*230	Customize
Net weight (kg)	Based on the actual weight				
Exterior material	Standard 1.5mm electrolytic plate electrostatic spray paint				
Interior material	Stainless steel plate SUS#304				
Temp Range	Type L: -40°C to 150°C; Type S: -70°C to 150°C; or customized				
Humid Range	20%RH to 98%RH				
Temp Fluctuation	±0.5°C				
Temp Variation in Space	±3°C (For equal and more than 100°C); ±2°C (For less than 100°C)				
T Pull Down Rate	0.7°C - 1°C/min				
Heat Up of Temp	0.7°C - 1°C/min				
Air Pressure Range	Normal pressure to 1kPa				
De-Pressure Rate	≥40kPa, ±2kPa; 4kPa-40kPa, ±0.5kPa; ≤4kPa, ±0.1kPa				
Pressure Recovery	Normal pressure to 1kPa ≤ 30 mins				
Configuration Interface	With USB, WLAN, RS232 port, APP function is optional				
Power supply	AC 380V 50Hz				